



# MASTER GEARMATIC

## API GL-5 SAE 85W90/85W140

MASTER GEARMATIC GL-5 IS A MULTI-VISCOSITY AND MULTI-PURPOSE EXTREME PRESSURE GEAR OIL BLENDED WITH HIGH QUALITY BASE OILS AND SELECTED & PHOSPHORUS ADDITIVES ALONG WITH ANTI-CORROSION AND ANTI-OXIDANT TO MEET API SERVICE CLASSIFICATION OF GL-5 FOR USE IN HYPOID AND SPIRAL BEVEL UNIT OPERATING UNDER VERY SEVERE OPERATING CONDITIONS.

EXCELLENT GEAR PERFORMANCE

SUPERIOR PROTECTION AGAINST WEAR

EXCELLENT PROTECTION AGAINST RUST AND CORROSION

COMPATIBLE WITH OTHER GEAR LUBRICANT

OUTSTANDING RUST INHIBITOR

GOOD LOAD CARRYING CAPABILITY

HIGH VISCOSITY INDEX

EXCELLENT LOW TEMPERATURE PERFORMANCE



### PHYSICAL CHARACTERSTICS

PROPERTIES	METHOD	TYPICAL VALUE	
		85W90	85W140
Kinematic Viscosity @ 100°C (cSt)	ASTM D 445	17.2	32
Viscosity Index	ASTM D 2270	98	98
Flash Point (COC) °C	ASTM D 92	200	210
Pour Point °C	ASTM D 97	-21	-18